

0.6/1kV RFOU 1C,2C,3C,4C [P1], [P1/P8]

Contact

Nexans Offshore Cable
Ju-Yong.PARK@nexans.com

- Power circuit below 1kV, Lighting circuits, Trace heating circuits.
- Fixed installation power, control & lighting both explosion risk and safe areas, general purposes.
- Maximum operating conductor temperature 90°C

DESCRIPTION

Construction Details

- Conductor : Circular tinned stranded copper as per IEC 60228, Class 2
- Insulation : Halogen Free Ethylene Propylene Rubber
- Cabling (with filler)
- Inner covering : Halogen free thermosetting compound
- Armour : Copper wire braid
- Outer sheath : Halogen-free thermosetting compound, SHF2 or SHF Mud

Standard Applied

- Design guideline : NEK 606-2009 & IEC 60092-353
- Material
- Insulation : HF-EPR as per IEC 60092-351
- Sheath : SHF2 as per IEC 60092-359
- Flame retardant : IEC 60332-3-22, Cat.A
- Halogen free properties : IEC 60754-1,2
- Low smoke properties : IEC 61034-1,2
- Mud resistant : NEK 606-2009
- Cold properties : CSA C22.2
- Sunlight resistance : UL 1581

Identification of color

- Insulation
- 1C : Grey
- 2C : Grey, Black
- 3C : Grey, Black, Red
- 3G : Grey, Black, Green/Yellow stripe
- 4C : Grey, Black, Red, Blue
- 4G : Grey, Black, Red, Green/Yellow stripe
- Note) Any other colors is applicable in accordance with the CENELEC Harmonization Document HD 308 S2

- Outer sheath : Black
- Note) Any other colors purchaser required

Type approval

- ABS, BV, DNV, LR



STANDARDS

International IEC 60092-351;
IEC 60092-353; IEC 60092-359;
IEC 60332-3 Cat.A;
IEC 60754-1; IEC 61034;
IEC 61034-2

National NEK 606



Rated Voltage U_o/U (Um)
0.6/ 1 (1.2) kV

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

Version Sang-Hwan.KIM Generated 8/27/18 www.nexans.co.kr Page 1 / 4

 Nexans

CHARACTERISTICS

Electrical characteristics

Rated Voltage U₀/U (Um)

0.6/ 1 (1.2) kV



Rated Voltage U₀/U (Um)
0.6/ 1 (1.2) kV

0.6/1kV RFOU 1C,2C,3C,4C [P1], [P1/P8]

Contact
Nexans Offshore Cable
Ju-Yong.PARK@nexans.com

PRODUCT LIST

Nb. of cores	Cross section [mm ²]	Av. insul. thickness [mm]	Inner sheath thick. [mm]	Diam. over inner sheath [mm]	Diam. over armour [mm]	Average sheath thickness [mm]	Nom. outer diam. [mm]	Approx. weight [kg/km]
1	1	1.0	1.0	5.1	6.2	1.0	8.4	120
1	1.5	1.0	1.0	5.4	6.5	1.1	8.9	135
1	2.5	1.0	1.0	5.8	6.9	1.1	9.3	150
1	4	1.0	1.0	6.4	7.5	1.1	9.9	180
1	6	1.0	1.0	6.9	8.0	1.1	10.4	205
1	10	1.0	1.0	7.9	9.0	1.2	11.6	270
1	16	1.0	1.0	8.9	10.0	1.2	12.6	350
1	25	1.2	1.0	10.7	12.3	1.3	15.1	535
1	35	1.2	1.0	11.9	13.5	1.3	16.3	655
1	50	1.4	1.0	13.6	15.2	1.4	18.2	825
1	70	1.4	1.0	15.5	17.1	1.5	20.3	1080
1	95	1.6	1.0	17.8	19.4	1.6	22.8	1410
1	120	1.6	1.0	19.4	21.0	1.6	24.4	1685
1	150	1.8	1.0	21.4	23.0	1.7	26.6	2020
1	185	2.0	1.0	23.6	25.2	1.8	29.0	2455
1	240	2.2	1.2	27.1	28.7	1.9	32.7	3155
1	300	2.4	1.2	29.9	31.5	2.1	35.9	3865
2	1	1.0	1.0	8.6	9.7	1.2	12.3	245
2	1.5	1.0	1.0	9.2	10.3	1.2	12.9	270
2	2.5	1.0	1.0	10	11.1	1.2	13.7	320
2	4	1.0	1.0	11.2	12.8	1.3	15.6	440
2	6	1.0	1.0	12.2	13.8	1.4	16.8	525
2	10	1.0	1.0	14.2	15.8	1.4	18.8	685
2	16	1.0	1.0	16.2	17.8	1.5	21.0	895
2	25	1.2	1.0	19.8	21.4	1.7	25.0	1295
2	35	1.2	1.0	22.2	23.8	1.8	27.6	1630
2	50	1.4	1.0	25.6	27.2	1.9	31.2	2085
2	70	1.4	1.2	29.8	31.4	2.1	35.8	2795
2	95	1.6	1.2	34.4	36.4	2.3	41.2	3780
2	120	1.6	1.4	37.8	39.8	2.4	44.8	4560
2	150	1.8	1.4	41.8	43.8	2.6	49.2	5500
2	185	2.0	1.4	46.2	48.2	2.7	53.8	6675
2	240	2.2	1.6	52.8	54.8	3.0	61.0	8605
2	300	2.4	1.6	58.4	60.4	3.2	67.0	10510
3	1	1.0	1.0	9.1	10.2	1.2	12.7	280
3	1.5	1.0	1.0	9.8	10.9	1.2	13.4	320
3	2.5	1.0	1.0	10.7	12.3	1.3	15.0	420
3	4	1.0	1.0	11.9	13.5	1.3	16.2	510
3	6	1.0	1.0	13	14.6	1.4	17.5	610

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

0.6/1kV RFOU 1C,2C,3C,4C [P1], [P1/P8]

Contact

Nexans Offshore Cable
Ju-Yong.PARK@nexans.com

Nb. of cores	Cross section [mm ²]	Av. insul. thickness [mm]	Inner sheath thick. [mm]	Diam. over inner sheath [mm]	Diam. over armour [mm]	Average sheath thickness [mm]	Nom. outer diam. [mm]	Approx. weight [kg/km]
3	10	1.0	1.0	15.2	16.8	1.5	19.9	830
3	16	1.0	1.0	17.3	18.9	1.6	22.2	1100
3	25	1.2	1.0	21	22.8	1.7	26.1	1560
3	35	1.2	1.0	24	25.4	1.8	29.3	2000
3	50	1.4	1.2	27.8	29.5	2.0	33.5	2620
3	70	1.4	1.2	31.9	34.0	2.2	38.4	3580
3	95	1.6	1.2	36.8	38.9	2.3	43.5	4700
3	120	1.6	1.4	40.6	42.6	2.5	47.7	5750
3	150	1.8	1.4	44.9	46.9	2.7	52.4	6960
3	185	2.0	1.6	50	52.0	2.9	57.9	8560
3	240	2.2	1.6	56.7	58.7	3.1	65.0	10940
3	300	2.4	1.8	63	64.9	3.4	71.9	13490
4	1	1.0	1.0	10	11.1	1.2	13.6	320
4	1.5	1.0	1.0	10.8	12.4	1.3	15.1	410
4	2.5	1.0	1.0	11.7	13.3	1.3	16.0	480
4	4	1.0	1.0	13.2	14.8	1.4	17.7	610
4	6	1.0	1.0	14.4	16.0	1.4	18.9	730
4	10	1.0	1.0	16.8	18.4	1.5	21.5	990
4	16	1.0	1.0	19.2	20.8	1.6	24.1	1330
4	25	1.2	1.0	23.3	25.2	1.8	28.6	1920
4	35	1.2	1.2	27	28.1	1.9	32.5	2500
4	50	1.4	1.2	30.9	33.0	2.1	37.2	3340
4	70	1.4	1.2	35.5	37.6	2.3	42.2	4440
4	95	1.6	1.4	41.3	43.3	2.5	48.4	5930
4	120	1.6	1.4	45.2	47.2	2.7	52.7	7210
4	150	1.8	1.6	50.4	52.4	2.9	58.3	8800
4	185	2.0	1.6	55.7	57.7	3.1	64.0	10760
4	240	2.2	1.8	63.5	65.4	3.4	72.4	13890
4	300	2.4	1.8	70.2	72.2	3.7	79.8	17405

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.