

The explosion proof photocell provides automatic control of the marine lights, aeronautical obstruction lights, helideck lights at dawn and dusk, when used in conjunction with the Navais Central Control Panel (NCCP).

Key features

- Reliable Marine external photocell
- Low cost of ownership
- Certified for Zone 1 and Zone 2 areas with gas explosion hazard
- Compact design
- Non metallic body
- Spacious cable connection compartment

Standards/Certification

- Cenelec EN 60079-0, EN 60079-7 and EN 60079-18
- KEMA 02ATEX2267 X; ATEX Ⓜ II 2G Ex e mb IIC T6 Gb
- Cenelec IEC 60079-0, IEC 60079-7 and IEC 60079-18
- IECEx DEK 11.0024X; Ex e mb IIC T6 Gb
- ABNT NBR IEC 60079-0, ABNT NBR IEC 60079-7 and ABNT NBR IEC 60079-18
- Inmetro NCC 17.0026 X

Performance characteristics

- Designed to work only in conjunction with Navais Central Control Panel (NCCP) concept

Electrical characteristics

- Operating voltage: Supply from Navais Central Control Panel (NCCP)
- Connection details: max. 2.5mm²; one M20x1.5 metal cable gland entry

Physical characteristics

- Dimensions (L x W x H): 117 x 80 x 57mm
- Weight: 0.5kg
- Degree of protection: IP66
- Operating temperature range: -50°C to +55°C

